ACVENTIS Phone: +49 211 4846 398 0 E-Mail: contact@acventis.de

RT112 10.1 Inch Android Rugged Tablet

5G & WLAN 6E | Longevity QCM5430 Processor | IP67 & 1.5M Drop

Powered by Android 13 OS with GMS & AER Certified

The RT112 is a 10.1-inch Android 13 rugged tablet equipped with an advanced 64-bit Hexa Cores CPU capable of reaching speeds up to 2.1 GHz. It effortlessly handles demanding tasks while ensuring smooth multitasking. With the distinction of Google Certification, encompassing Google Mobile Service (GMS) and Android Enterprise Recommended (AER) endorsement, the dual certification assures a secure and efficient business environment.

Seamless and Connectivity via Wireless Communication

Featuring Bluetooth® 5.2, wireless WLAN 6E with fast roaming and 5G connectivity for real-time data collection, user can scan the item and instantly connect to the backend system to find out the quantity in stock or make an online order for customers. The RT112 delivers a seamlessly work experience and improves productivity for various applications, making it faster downloads and uploads at user's fingertips on the most reliable networks for your business.

5G IOT Platform

Equipped with the Qualcomm 5430 5G IoT Platform, the RT112 offers seamless integration into the future of technology. Its robust 5G capabilities ensure lightning-fast data transfer and a responsive online experience, all while being optimized for the demands of the Internet of Things. With a focus on longevity, the RT112 boasts an extended life cycle, making it an ideal investment for those seeking a device that will remain relevant and efficient for years to come.

Durable Design

The RT112 enhances the industrial durable protection with features including IP67 dustproof, waterproof, and 1.5 meters resistance to fall protection. That means it covers fully protected from dust and can survive in 1 meter of water for up to 30 mins. The MIL-STD-810H standard assures an overall environmental vibration and humidity. The light tablet with a slim 12mm edge is designed for workers to comfortably capture data and check inventory in high portability from day to night. For an easy touch and view, the 10.1 "display supports glove and wet touch mode with 450 nits.

Features

- · Android 13 with GMS & AER Certified
- 10.1" (1920 x 1200) LCD display with Gorilla® Glass (450 nits)
- Lightweight but durable: 690g with 12mm
- Rugged Design: IP67 rated, 1.5M drop and MIL-STD-810H certified
- Wireless Communication: 5G & WLAN 6E
- 5G IOT Platform (Qualcomm 5430): Support Long Life Cycle





ACVENTIS Phone: +49 211 4846 398 0 E-Mail: contact@acventis.de

RT112 Specifications

	System Feat	IFAS		Symbologies			
	OS			1D	Codabar	Code 11, Code 128, Code 2 of 5, Code 39, Code 93	
	GMS certified	GMS certified				EAN/JAN-13, EAN/JAN 8, IATA Code 2 of 5, Interleaved	
	CPU	Qualcomm Snapdragon™ 5430 Processor, 64bits,				atrix 2 of 5, MSI, GS1 Databar, UPC-A, UPC E,	
	0.0	Hexa Cores up to 2.1 GHz (Option: Octa Cores)				AN-13 with Extended Coupon Code, Coupon GS1 Code	
	Memory	6GB RAM + 128GB Flash			32 (PARA	AF), EAN-UCC Emulation, GS1 Data Bar	
		(Option: 8GB RAM + 128GB Flash)		2D	Codabloc	k A, Codablock F, PDF417, MicroPDF417, Aztec Code,	
	AI	6th Gen Qualcomm AI Engine			Data Mat	rix, MaxiCode, QR Code, Chinese Sensible (Han Xin),	
	Others	Qualcomm® Trusted Execution Environment (TEE)			Grid Matr	rix, Dot Code	
				Postal	Australiar	n Post, British Post, Canadian Post, China Post,	
	Display				Japanese	Post, Korea Post, Netherlands Post, Planet Code,	
	10.1" (1920 x 1200) LCD Display 450 nits				Postnet		
	Gorilla® Glass, Multi-Touch User Interface with Capacitive, stylus,			Communication			
	glove, wet-finger Compatibility			Camera	Rear:13M	1 (with auto-focus and LED flash, Support Google Arcore	
				Gumoru	& Depth		
	Buttons / Key	rpad 🛛 🖌 Indicator				(with fixed focus)	
	6 Physical Buttor	LEDs, Vibrator		Bluetooth®	Bluetooth	ո [®] 5.2	
	Power, Volume+ Programable Key			WLAN		E, 2.4GHz & 5GHz & 6GHz	
	FIOGRAFIADIE Key	X 1			Support [Dual-Band Simultaneous (DBS)	
					IEEE 802	.11a/b/g/n/ac/d/h/i/k/r/v/ac/ax (2x2 MU-MIMO)	
	RFID			WWAN (Optional)	5G FR1 S	Sub 6GHz:	
	Support HF/NFC				N1/N2/N3	3/N5/N28/N41/N48/N66/N71/N77/N78/N79 (4x4 MIMO)	
	ISO14443-4 (Typ	e A, Type B), ISO15693, Mifare, Felica(ISO/IEC18092)				FDD) – Bands 1, 2, 3, 4, 5, 7, 8, 12, 13, 17, 20, 28, 66, 71	
)) – Bands 38, 39, 40, 41	
	I/O Interfaces					S/HSPA+ – Bands 1, 2, 5, 8	
	•					'GPRS/EDGE (850/900/1800/1900 MHz) 2G/3G/4G/5G	
	POGO PIN	USB3.1 Type-C x 1 POGO pin		GPS		Dou, Glonass, Galileo, QZSS, NavIC and SBAS	
	SIM Slot	Nano SIM x 1				AN model only)	
	Expansion Slot	Micro SD Card x 1		Sensors		be, Accelerometer (G-sensor), E-compass, Light &	
	Audio	Dual-speakers			Proximity		
		MIC*2		E de la com			
		(noise cancelling & Background noise depression)		Enclosure			
				Dimensions		0x165x12mm	
	Power Source	Power Source		Weight	69	00g	
	Main Battery	z 8800mAh (removable)					
	Main Dattery			Environment			
	Software			Operating temperatu	ire -20	0°C ∼ 55°C	
		oftware Solutions and utilities such as Airwatch, SOTI,		Storage temperature		0°C ~ 70°C	
	Ivanti Wavelink, a			Drop test to Concrete		5m	
				Environmental Sealin	•		
	Regulatory A	oprovals		Vibration and Shock 1	เซรเ M	IL-STD-810H, Method 516.8, Procedure IV	
		IC, NCC, BSMI, VCCI, TELEC, CCC, SRRC, BQB, RoHS,					
	REACH			What comes in t	the box	 Accessories 	
				RT112		Rotatable Hand Strap	
_				Battery Pack USB-C Adaptor		Shoulder Strap Screen Protector	
5	🕢 🗘	unitech 🔨		COD C Adaptor		Office Cradle	
	SGS UKAS	Green Product				Vehicle Cradle	
	Headquarters	3				Capacitive Stylus Pen (5.5mm) w/ Coil Strap	
	Taipei, Taiwan http://www.ute.	com e-mail: info@hg.ute.com					
		·		unitech Europe			
	unitech America Los Angeles http://us.ute.com e-mail: info@us.ute.com			Tilburg / Netherland	s e-mail: info@eu.ute.com		
	http://can.ute.co Mexico	m info@can.ute.com		unitech Japan Tokyo			
	http://latin.ute.com e-mail: info@latin.ute.com				e-mail: info@	e-mail: info@jp.ute.com	

unitech Asia Pacific & Middle East Taipei http://apac.ute.com info@apac.ute.com / info@india.ute.com http://mideast.ute.com info@mideast.ute.com unitech Greater China Beijing, Shanghai, Guang Zhou, Xiamen http://cn.ute.com info@cn.ute.com Taipei http://tw.ute.com info@tw.ute.com



Specifications subject to change without notice. Copyright 2023 unitech Electronics Co., Ltd. All rights reserved. unitech is a registered trademark of unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.

