

Zebra® ZXP Series 7™ Card Printer



SEE MORE. DO MORE.



The fast and reliable ZXP Series 7 prints photo-like cards for medium- to high-volume applications

Utilising the latest in card-printing technology, the ZXP Series 7 card printer provides high-quality card printing. The printer delivers fast yet reliable performance whilst offering users exceptional value by lowering the printer's total cost of ownership. Time after time, it prints sharp vivid cards with precise colour control.

The ZXP Series 7 printer has an innovative design. It automatically adjusts to the thickness of the card, and ribbon loading is easy.

With colour-coded guides and a clear LCD control panel, it's simple for anyone to use.

Choose from numerous encoding, connectivity and ribbon options, and if extra security or durability is needed for cards, wasteless single- or dual-sided lamination is also available.

Locking mechanisms protect the printer and media, and software provides further security by tracking and restricting activities as required.

Ideal for These Applications

High-volume Environments:
service bureaus, identification cards, loyalty/membership cards, access control

High-security Industries:
government credentials, secure access control, financial services

Other Industries:
education, gaming, healthcare, hospitality, retail, sports & entertainment

Zebra supplies make it easier than ever to manage your printer

Genuine Zebra™ supplies meet stringent quality standards, and are recommended for optimal printing quality and proper printer performance. The ZXP Series 7 printer is designed to work only with Zebra True Colours® ix Series™ ribbons and Zebra True Secure™ i Series laminates.

For more information, visit www.zebra.com/zxpseries7



CHOOSE THE ZXP SERIES 7 PRINTER FOR PERFORMANCE, PRODUCTIVITY, ADAPTABILITY AND COST EFFICIENCY

Performance: works the way you need it – card after card

The ZXP Series 7 printer is built to meet the needs of today's demanding business environment.

- Robust design that works out of the box in a wide range of environments and applications
- Generates near-photographic print quality and colour depth using photo-print technology
- Edge-to-edge card printing
- Laminator ensures security of the cards and lengthens the life of the image

Productivity: high speeds and low maintenance

The ZXP Series 7 printer features fast print speeds that improve productivity and reduce wait time.

- Fast click-to-drop and batch print speeds
- Up to three jobs can be in process at the same time (encoding, printing and laminating simultaneously), enabling fastest throughput
- ix Series™ ribbons are developed for faster printing
- Simultaneous dual-sided lamination

Ease of integration and low maintenance are ensured by:

- High-capacity media
- Ribbon and laminate rolls are synchronized
- Simplified ribbon loading and operation
- Windows® drivers, ZMotif™ SDK and networking options for faster deployment

Adaptability: meet business needs – now and in the future

The ZXP Series 7 printer offers real flexibility. You can select options whenever you need them – so you can add to your portfolio of card-printing applications and manage your investment at the same time.

Options include:

- Single- or dual-sided printing
- Numerous encoding and connectivity options, including UHF encoding and 802.11b/g wireless connectivity
- Wasteless single- or dual-sided lamination
- Integrated barcode reader
- Zebra Duo-Print™ dual-sided printing upgrade kit
- A variety of ribbon options

Adaptability and control through software:

- ZXP Toolbox provides advanced control over printer, driver, and software setup; administration; and diagnostics
- Advanced security features allow administrative flexibility for customising the feature sets and privileges for users
- The ZMotif SDK allows software developers to easily integrate advanced features or write their own custom print applications

Cost efficiency: supplies designed to minimize the cost per card

The ZXP Series 7 printer is designed to work with Zebra True Colours ix Series ribbons and Zebra True Secure i Series laminate. The high-capacity ribbons reduce costs by delivering more images per roll and feature an improved formulation for printing high-quality images at higher speeds. Many ribbon types are available in two sizes to meet the needs of every printing task.

Zebra True Secure laminates reduce the risk of counterfeiting and extend the life of your high-security cards. The unique laminate design dramatically reduces waste by eliminating the need for carrier material, backings and liners. Specially designed cartridges make laminate replacement simple.

Both the ribbons and laminates utilise intelligent media technology, which automatically detects and calibrates the printer.



HIGH-PERFORMANCE SOFTWARE FOR HIGH-PERFORMANCE HARDWARE

Zebra CardStudio™

Whether you are a small business or a large enterprise, Zebra's CardStudio makes designing and printing professional-looking cards easy. It lets you make the most of ZXP Series 7 printer's functionality, including smart-card encoding and laminating.

Flexible single or multiple user network licensing and database integration options make CardStudio the ideal card-design software complement for the ZXP Series 7 printer.

For more information visit:
www.zebra.com/cardstudio

Zebra Virtual PrintWare™

Zebra Virtual PrintWare is designed to make it easy to issue cards from your own applications. The template-based printing capability allows for easy third-party application integration of card printing and card production flow.

You can print to one or more networked card printers, and remotely monitor printers' health and status. To increase print capacity and throughput, you can also use the software to pool and manage multiple printers as if they were one printer.

For more information visit:
www.zebra.com/virtualprintware



SPECIFICATIONS AT A GLANCE*

Printer Name

ZXP Series 7

Standard Features

- 300 dpi/11.8 dots per mm print resolution
- USB 2.0 and Ethernet 10/100 connectivity
- Microsoft® Windows Certified drivers
- 200-card capacity feeder (30 mil)
- 15-card reject hopper (30 mil)
- 100-card output hopper (30 mil)
- Single-card feed capability
- ix Series intelligent media technology
- 21-character x 6-line LCD operator display with configurable soft keys
- Kensington® physical lock slot
- Two-year unlimited warranty on printer and printhead

Optional Features

- Single-sided laminator
- FIPS 201 compliant dual-sided laminator
- Lockable enclosures and card feeder**
- Extended product warranty programmes
- 802.11b/g wireless connectivity
- 1D barcode scanner
- Duo-Print upgrade kit

NOTE: FIPS201 compliant dual-sided laminator is only for North America.

Printing and Laminating Specifications

- Color dye sublimation or monochrome thermal-transfer printing
- Single- and dual-sided printing
- Near photographic print quality
- Edge-to-edge printing on standard CR-80 media
- Simultaneous printing, encoding, and laminating capability
- One-pass single- and dual-sided wasteless lamination
- 1375 cards/hour monochrome single-sided or 555 cards/hour dual-sided printing
- 300 cards/hour full-colour YMCKO single-sided printing
- 225 cards/hour full-colour YMCKOK dual-sided printing
- 270 cards/hour full-colour YMCKO single-sided printing with lamination
- 200 cards/hour full-colour YMCKOKO dual-sided printing with lamination

NOTE: Printing throughput (cards per hour) based on batch printing with USB connectivity. Times may vary depending on the computer configuration.

Encoding Options and Specifications

- Magnetic stripe encoder – AAMVA and ISO 7811 (new and pre-encoded, tracks 1, 2, and 3, high and low coercivity)
- ISO 7816 Smart Card Contact Station for third-party external contact encoders
- Combined MIFARE® ISO 14443 A & B (13.56MHz) contactless and ISO 7816 Contact Encoder with EMV level 1 certification, and PC/SC compliance (supported over USB and Ethernet)
- EPCglobal® Gen 2 UHF RFID encoder

Supplies Specifications

- Zebra's intelligent technology RFID tags authenticate and automate ix Series ribbons and i Series laminates
- Card cleaning rollers included with each ribbon carton
- Specially designed cleaning supplies simplify preventative maintenance

True Colours ix Series Ribbons

- YMCKO: 250 or 750 images/roll
- YMCUVK: 750 images/roll
- YMCKOK: 250 or 750 images/roll
- 1/2-panel YMC, full KO: 1250 images/roll
- KdO and KrO: 2000 images/roll
- WrKr: 2000 images/roll
- Blue, red, gold, silver monochrome: 5000 images/roll
- Black monochrome: 2500 or 5000 images/roll
- White monochrome: 4000 images/roll
- Scratch-off gray: 3250 images/roll
- Other colours available on request

True Secure i Series Laminates

- Linerless waste-free 1.0 mil top and bottom laminate: 750 images/roll
- Laminate types: clear, magnetic stripe, smart card, and holographic wallpaper designs
- Custom laminates with registered or wallpaper holographic images available on request

Card Specifications/Compatibility

- Card thickness: 10–50 mil (0.25–1.27mm)
- Card thickness for lamination: 30 mil (0.76mm)
- Card size: CR-80, ISO 7810 format, Type ID-1
- Card material: PVC and composite, ABS cards, PET, PET-G, PET-F, PETix, and Teslin® composite
- Technology cards: contact and contactless smart cards
- Specialty cards: adhesive backed, signature panel, transparent cards with IR-blocker

NOTE: For optimum print quality and printer performance, use genuine Zebra™ supplies.

Software

- ZMotif SDK support and sample code
- Microsoft Windows Certified printer drivers with Toolbox utility features: Windows XP (32 bit), Vista (32 and 64 bit), Server 2003 (32 bit), Windows 7 (32 and 64 bit), Server 2008 (32 and 64 bit), Windows 8 and Win 8 Pro (32 and 64 bit), Server 2012 (64 bit)
- CardStudio card design and issuance software
- Zebra Virtual PrintWare software support

NOTE: Please see www.zebra.com for up to-date listing of supported systems.

Communications Interfaces

- USB 2.0
- USB supports plug-and-play printer identification
- 10/100 Ethernet
- IPv6-ready Ethernet**
- 802.11b/g wireless option

Electrical Specifications

- Auto-switching single-phase AC power
- 90V–264V AC and 47–63Hz (50–60Hz nominal)
- FCC Class A

Physical Characteristics

- Height: 306mm / 12"
- Width (printer only): 699mm / 27.5"
- Width (printer with laminator): 964mm / 38"
- Depth: 277mm / 10.9"
- Weight (printer only): 12.2kg / 26.9lbs
- Weight (printer with laminator): 17.9kg / 39.5lbs

Environmental

- Operating temperature: 15°C / 59°F to 35°C / 95°F
- Storage temperature: -5°C / 23°F to 70°C / 158°F
- Operating humidity: 20% to 80% inclusive, non-condensing
- Storage humidity: 10% to 90% inclusive, non-condensing
- Media should be stored away from direct sunlight, between +5° and +30°C, and between 30% to 50% relative humidity



Zebra Technologies – EMEA Headquarters & Sales Office

Zebra Technologies Europe Limited, Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5XF, United Kingdom
Telephone: +44 (0)1628 556000 **Fax:** +44 (0)1628 556001 **Email:** mseurope@zebra.com **Web:** www.zebra.com

Other EMEA Locations

Europe: France, Germany, Italy, the Netherlands, Poland, Russia, Spain, Sweden, Turkey
Middle East & Africa: Dubai, South Africa

Zebra® ZXP Series 7™ Pro Service Bureau Card Printer

OPTIMIZING ON-SITE CARD PRODUCTION SERVICES

The Zebra® ZXP Series 7 Pro meets today's increasing need for service bureaus and governments to quickly set up and issue secure, reliable forms of identification while improving the efficiency and speed of large print jobs. The ZXP Series 7 Pro is simple to use, produces more cards in less time and is less expensive to own than any other printer in its category.



The ZXP Series 7 Pro is ideal in:

Healthcare and Education

- Employee and student ID cards; Employee access control cards

Hospitality and Retail

- Gaming; Loyalty; Membership; Gift cards; Sports; Entertainment

High Security

- Government credentials; Secure access control; Financial services

ZXP Series 7 Pro is specifically designed and configured to meet the needs of high volume Card printing.

Reliable performance and photo-quality printing

Like the ZXP Series 7, the ZXP Series 7 Pro version delivers the same fast yet reliable performance and prints sharp, vivid cards with photo-quality images. With available features like single- or dual-sided printing, encoding and connectivity options, as well as locking mechanisms for security, the ZXP Series 7 Pro is flexible to meet business needs now and in the future.

High-capacity hoppers

The ZXP Series 7 Pro has input and output hoppers capable of holding up to 250 plastic cards at one time, eliminating the need for constant staff oversight. The cards in the output hopper are stacked in first-in, first-out order, thereby eliminating the need for sorting cards once the print job is completed. Both the input and output hoppers are removable for quick and easy card reloading.

Synchronized supplies

The high-capacity input and output hoppers are synchronized with high-capacity ribbon options. The result? Less operator time spent replacing supplies and fewer production interruptions leading to more efficient operations and cost savings.

ZXP SERIES 7 PRO — WHEN YOU NEED FAST, RELIABLE, HIGH-VOLUME CARD PRINTING.

FOR MORE INFORMATION, VISIT WWW.ZEBRA.COM/ZXP SERIES 7 PRO OR
OUR GLOBAL CONTACT DIRECTORY AT WWW.ZEBRA.COM/CONTACT

ZXP SERIES 7 PRO SPECIFICATIONS AT-A-GLANCE

STANDARD FEATURES

- 300 dpi/11.8 dots per mm print resolution
- USB 2.0 and Ethernet 10/100 connectivity
- Magnetic stripe encoder — AAMVA and ISO 7811 (new and pre-encoded, tracks 1, 2, and 3, high and low coercivity)
- Microsoft® Windows Certified drivers
- 250-card input capacity feeder (30 mil)
- 15-card reject hopper (30 mil)
- 250 First-in, First-out mechanical output hopper
- Single-card feed capability
- ix Series intelligent media technology
- 21-character x 6-line LCD operator display with configurable soft keys
- Kensington® physical lock slot
- License key for Zebra Virtual PrintWare PrintMonitor software for monitoring of Network Attached Card Printers.
- Two-year unlimited warranty on printer and printhead

OPTIONAL FEATURES

- FIPS 201 compliant dual-sided laminator
- Optional contact/contactless SmartCard encoding option module
- Lockable enclosures and card feeder
- Extended product warranty programs
- 802.11b/g wireless connectivity
- 1D barcode scanner

NOTE: FIPS201 compliant dual-sided laminator is only for North America.

PHYSICAL CHARACTERISTICS

Dimensions	Printer only: 13.75 in. H x 10.9 in. D x 28.25 in. W 349 mm H x 277 mm D x 718 mm W Printer with laminator: 13.75 in. H x 10.9 in. D x 43 in. W 349 mm H x 277 mm D x 1092 mm W
Weight	Weight (printer only): 31.7 lbs/14.4 kg Weight (printer with laminator): 44.3 lbs/20.1 kg

ENVIRONMENT

Operating Temp.	59° F to 95° F/15° C to 35° C
Storage Temp.	23° F to 158° F/-5° C to 70° C
Operating Humidity	20% to 80% inclusive, non-condensing
Storage Humidity	10% to 90% inclusive, non-condensing

PRINTING AND LAMINATING SPECIFICATIONS

- Color dye sublimation or monochrome thermal-transfer printing
- Single- and dual-sided printing
- Near photographic print quality
- Edge-to-edge printing on standard CR-80 media
- Simultaneous printing, encoding, and laminating capability
- One-pass single- and dual-sided wasteless lamination
- 1375 cards/hour monochrome single-sided or 555 cards/hour dual-sided printing
- 300 cards/hour full-color YMCKO single-sided printing
- 225 cards/hour full-color YMCKOK dual-sided printing
- 270 cards/hour full-color YMCKO single-sided printing with lamination
- 200 cards/hour full-color YMCKOKO dual-sided printing with lamination

NOTE: Printing throughput (cards per hour) based on batch printing with USB connectivity. Times may vary depending on the computer configuration.

ENCODING OPTIONS AND SPECIFICATIONS

- MISO 7816 Smart Card Contact Station for third-party external contact encoders
- Combined MIFARE® ISO 14443 A & B (13.56MHz) contactless and ISO 7816 Contact Encoder with EMV level 1 certification, and PC/SC compliance (supported over USB and Ethernet)
- EPCglobal® Gen 2 UHF RFID encoder

SUPPLIES SPECIFICATIONS

- Zebra's intelligent technology RFID tags authenticate and automate ix Series ribbons and i Series laminates
- Card cleaning rollers included with each ribbon carton
- Specially designed cleaning supplies simplify preventative maintenance

True Colors ix Series Ribbons	<ul style="list-style-type: none"> • YMCKO: 250 or 750 images/roll • YMCUVK: 750 images/roll • YMCKOK: 250 or 750 images/roll • ½-panel YMC, full KO: 1250 images/roll • KdO and KrO: 2000 images/roll • WrKr: 2000 images/roll • Blue, red, gold, silver monochrome: 5000 images/roll • Black monochrome: 2500 or 5000 images/roll • White monochrome: 4000 images/roll • Scratch-off gray: 3250 images/roll • Other colors available on request
True Secure i Series Laminates	<ul style="list-style-type: none"> • Linerless waste-free 1.0 mil top and bottom laminate: 750 images/roll • Laminate types: clear, magnetic stripe, smart card, and holographic wallpaper designs • Custom laminates with registered or wallpaper holographic images available on request
Card Specifications/Compatibility	<ul style="list-style-type: none"> • Card thickness (unlaminated): 10 - 50 mil (0.25 - 1.27 mm) • Card thickness for lamination: 30 mil (0.76 mm) • Card size: CR-80, ISO 7810 format, Type ID-1 • Card material: PVC and composite, ABS cards, PET, PET-G, PET-F, PETix, and Teslin® composite • Technology cards: contact and contactless smart cards • Specialty cards: adhesive backed, signature panel, transparent cards with IR-blocker <p>NOTE: For optimum print quality and printer performance, use genuine Zebra™ supplies.</p>

SOFTWARE

- Includes license key for Zebra Virtual PrintWare PrintMonitor software for monitoring of Network Attached Card Printers.
- ZMotif SDK support and sample code
- Microsoft Windows Certified printer drivers with Toolbox utility features: Windows XP (32 bit), Vista (32 and 64 bit), Server 2003 (32 bit), Windows 7 (32 and 64 bit), Server 2008 (32 and 64 bit), Windows 8 and Win 8 Pro (32 and 64 bit), Server 2012 (64 bit), Windows 10
- CardStudio card design and issuance software
- Zebra PrintWare PrintManager software support

NOTE: Please see www.zebra.com for up-to-date listing of supported systems.

COMMUNICATIONS INTERFACES

USB 2.0: supports plug-and-play printer identification, 10/100 Ethernet, 802.11b/g wireless option

ELECTRICAL SPECIFICATIONS

Auto-switching single-phase AC power, 90V–264V AC and 47–63Hz (50–60Hz nominal), FCC Class A

ZEBRA SYNCHRONIZED SUPPLIES FOR OPERATIONAL EFFICIENCY AND LOWER COSTS

	Ribbon Media	250 Card capacity input and output hopper
Color Print Operations	750 Images per ribbon	3X synchronized card input and output: 250 cards (x3) = 750 = 3 full card feeder cassettes per YMCKO ribbon
Mono Print Operations	5,000 images per ribbon	20X synchronized card input and output: 250 Cards (x20) = 5000 = 20 full card feeder cassettes per black mono ribbon



NA and Corporate Headquarters
 +1 800 423 0442
inquiry4@zebra.com

Asia-Pacific Headquarters
 +65 6858 0722
contact.apac@zebra.com

EMEA Headquarters
zebra.com/locations
mseurope@zebra.com

Latin America Headquarters
 +1 847 955 2283
la.contactme@zebra.com